

**155 Mb/s, SFP LC Package, BIDI  
TX 1310/RX1550, TX 1550/RX1310 nm  
Multimode, 2 km Distance**



**Description**

The bi-directional (BIDI) transceiver product is unique in that only one single fiber (single mode or multimode) is required to transmit and receive signals simultaneously. That means the total bandwidth capacity of an existing cable infrastructure can be doubled instantly. The typical design of a BIDI transceiver uses a 1310 nm LD to transmit and 1550 nm PD to receive, and vice versa for the matching one (1310 nm to receive and 1550 nm to transmit) at the other end to make a complete link.

OptixCom's SFP transceivers are compliant with SFP Multi-Source Agreement (MSA). The BIDI transceivers utilize advanced filter optics to separate the two wavelength with more than 40 dB of isolation. These transceivers operate at 155 Mb/s for 2 km transmission distance with multimode fibers. The products are RoHS compliant.




Lead-Free

**BD7-155T3R5-ATM2K  
BD7-155T5R3-ATM2K**



155 Mb/s, 2<sup>23</sup>-1 NRZ Data Eye pattern



**Key Features**

- Multimode, 155 M/s data rate
- TX1310/RX1550 and TX1550/RX1310 nm wavelength
- 2 km reach and single 3.3 V power supply
- 18 dB power budget
- Z-axis hot pluggable
- SFF-8472 MSA Compliant
- Single LC connector optical interface
- AC coupling LVPECL differential I/O logics
- TTL RX\_LOS signal detect to monitor optical signals
- -40–85 °C extended temperatures available
- RoHS compliant

**Applications**

- ✓ FTTH, FTTX, ATM/SONET OC-3, SDH STM-1
- ✓ High speed I/O for file server
- ✓ Media converter, bus extension
- ✓ Central offices routers and switches
- ✓ Mass storage systems interconnect
- ✓ Computer cluster cross-connect

**Ordering Information**

**Part Number:** BD7-155T3R5-ATM2K  
155 Mb/s, Multimode, SFP BIDI Transceiver, TX 1310 nm and RX 1550 nm, 2 km reach, 0 – 70 °C.

**Part Number:** BD7-155T5R3-ATM2K  
155 Mb/s, Multimode, SFP BIDI Transceiver, TX 1550 nm and RX 1310 nm, 2km reach, 0 – 70 °C.

Add "-T" in the Part Number for extended temperature range -40–85 °C, i.e., BD7-155T3R5-ATM2K-T.

**Operating Conditions**

Parameter	Min.	Typical	Max.	Units
Operate Temperature	0	25	70	°C
- T Transceivers	-40	25	85	°C
Data Rate	---	155	200	Mb/s
Supply Voltage	3.1	3.3	3.5	V

**BD7-155T3R5-ATM2K-T**  
**BD7-155T5R3-ATM2K-T**

**Absolute Maximum Ratings**

Parameter	Symbol	Min.	Max.	Units
Storage Temperature	$T_{st}$	-40	85	°C
Supply Voltage	$V_{cc}$	-0.5	4.0	V
Input Voltage	$V_{in}$	-0.5	$V_{cc}$	V
Operating Current	$I_{op}$	---	300	mA

**Transmitter Electro-Optical Characteristics (FP Laser)**

Parameter	Symbol	Min.	Typical	Max.	Units
Differential Input Voltage <sup>1</sup>	$\Delta V_i$	0.4	---	2.0	V
Differential Input Impedance <sup>2</sup>	$Z$	---	100	---	ohm
Rise/Fall Time (10% - 90%)	$T_r/T_f$	---	1	2	ns
Optical Output Power <sup>3</sup>	$P_o$	-10	---	0	dBm
Optical Wavelength (BD7-155T3R5-ATM2K)	$\lambda_o$	1260	1310	1360	nm
Optical Wavelength (BD7-155T5R3-ATM2K)	$\lambda_o$	1480	1550	1580	nm
Extinction Ratio	$ET$	8.2	---	---	dB
Spectral Width (rms)	$\Delta\lambda$	---	---	7	nm
TX Disable Voltage – High	$V_{DH}$	2.4	---	$V_{cc}$	V
TX Disable Voltage - Low	$V_{DL}$	0	---	0.5	V
TX Fault Output - High	$V_{FH}$	2.4	---	$V_{cc}$	V
TX Fault Output - Low	$V_{FL}$	0	---	0.5	V
TX Disable Assert Time	$T_{ass}$	---	---	10	$\mu s$
TX Disable Deassert Time	$T_{disass}$	---	---	1.0	ms
Time to Initialize	$T_{as}$	---	---	300	ms
TX Fault from Fault to Assertion	$T_{fault}$	---	---	100	$\mu s$
TX Disable Time to Start Reset	$T_{reset}$	10	---	---	$\mu s$

Notes:

1. Module is designed for AC LVPECL coupling. See the design guide for proper termination.
2. Single ended will be 50 ohm for each signal line.
3. Output of coupling optical power into 50/125 or 62.5/125  $\mu m$  MMF.

**Class 1 Laser Product**  
Complies with  
**21 CFR 1040.10 and 1040.11**



### Receiver Electro-Optical Characteristics

Parameter	Symbol	Min.	Typical	Max.	Units
Differential Output Voltage <sup>1</sup>	$\Delta V_o$	0.5	---	1.2	V
Differential Input Impedance <sup>2</sup>	$Z$	---	100	---	Ohm
Optical Return Loss	OL	14	---	---	dB
Operating Wavelength (BD7-155T3R5-ATM2K)	$\lambda_c$	1480	---	1600	nm
Operating Wavelength (BD7-155T5R3-ATM2K)	$\lambda_c$	1260	---	1360	nm
Receiver Overload	$P_{max}$	0	---	---	dBm
Receiver Sensitivity <sup>3</sup>	$P_i$	---	---	-28	dBm
RX Signal Loss – Asserted	$P_{RL+}$	---	---	-28	dBm
RX Signal Loss – Deasserted	$P_{RL-}$	-45	---	---	dBm
Rise/Fall Time (10% - 90%)	$T_r/T_f$	---	1	2	ns
Signal Detect Hysteresis	$P_{SD+} - P_{SD-}$	1	---	---	dB
Crosstalk		---	---	-40	dB
RX Signal Loss Output - High	$V_{RL+}$	2.4	---	$V_{cc}$	V
RX Signal Loss Output - Low	$V_{RL-}$	0	---	0.5	V
RX Signal Loss Assert Time	$T_{RL+}$	---	---	100	$\mu$ s
RX Signal Loss Deassert Time	$T_{RL-}$	---	---	100	$\mu$ s
Serial ID Clock Rate	$f_c$	---	---	100	kHz

Notes:

1. Module is designed for AC LVPECL coupling. See the design guide for proper termination.
2. Single ended will be 50 ohm for each signal line.
3. Test at 155 Mb/s, 2<sup>23</sup> – 1 PRBS data pattern, and > 1x10<sup>-10</sup> of Bit-Error-Rate (BER).
4. Optical eye diagram is compliant with Telcordia GR-253-CORE and ITU-T G-957 standard.
5. Maximum supply current for the transceiver from V<sub>cc</sub> is 200 mA.

**Class 1 Laser Product**  
Complies with  
**21 CFR 1040.10 and 1040.11**

