

10 Gb/s, 1550 nm Single Mode, 40 and 80 km XENPAK Dual SC Package

Description

OptixCom's XENPAK fiber optics transceiver is designed with advanced 1550 nm EA-DFB laser and high speed electronics to achieve the optimum performance for optical interconnect applications. It is compliant with the XENPAK Multi-Source Agreement (MSA).

XENPAK uses 70-pin hot pluggable electrical connector and supports four lane XAU1 (10 Gigabit attachment unit interface) at both Ethernet (3.125 Gb/sec) and/or Fiber Channel (3.1875 Gb/sec) rates.

The transceiver uses duplex SC connector for the optical interface. The transceiver has >15 dB of power budget for 40 km and >24 dB for 80 km of transmission distance with single mode fibers. The product is RoHS compliant. Total power consumption is < 4W.



Lead-Free



XEN-10000EX-ATXXK
(**XX** = 40, 80)



10 Gb/s, 2³¹-1 NRZ data eye pattern

TX

RX



Key Features

- Standard XAU1 interface with 3Gb/s per channel
- 1550 nm single mode, 40/80 km, 10 Gb/s data rate
- > 15 dB power budget for 40 km
- > 24 dB power budget for 80 km
- Duplex SC connector optical interface
- 70-pin Z-axis hot pluggable connector
- AC coupling CML differential I/O logics
- Compliant with XENPAK MSA standard
- Compliant with IEEE 802.3ae, 10GBASE-ER/ZR
- Compliant with 10G FC Fiber Channel Standard
- RoHS compliant

Applications

- ✓ 10G Fiber Channel & Ethernet
- ✓ OC192/STM-64 for SONET/SDH
- ✓ High speed I/O for file server
- ✓ Data Communication for SAN and LAN
- ✓ Central offices routers and switches
- ✓ Mass storage systems interconnect
- ✓ Computer cluster cross-connect

Ordering Information

Part Number: XEN-10000EX-AT**XX**K

Description:

1550 nm 10 Gb/s, single mode, XENPAK fiber optics transceiver, **XX** km reach, 0-70°C.

XX = 40, 80.

Operating Conditions

Parameter	Min.	Typical	Max.	Units
Operate Temperature	0	25	70	°C
Data Rate	9.95	---	11.3	Gb/s
Supply Voltage (3.3V)	3.1	3.3	3.5	V
Supply Voltage (5V)	4.75	5	5.25	V
Adaptable Power Supply	1.15	1.2	1.25	V
Module Power Dissipation	---	---	4	W

Absolute Maximum Ratings

Parameter	Symbol	Min.	Max.	Units
Storage Temperature	T_{st}	-20	85	°C
Supply Voltage @ 3.3V	V_{cc3}	-0.5	4.0	V
Supply Voltage @ 5V	V_{cc5}	-0.5	6.0	V
Supply Voltage (APS)	V_{aps}	0	1.5	V
Humidity	$R.H.$	0	85	%

General Transmitter Characteristics

Parameter	Symbol	Min.	Typical	Max.	Units
XAUI Data Rate	X_{DR}	---	3.125	---	Gb/s
XAUI Baud Rate Tolerance	X_{BRT}	-100	---	+100	ppm
Differential Input Voltage ¹	ΔV_i	0.2	---	1.6	V
Differential Input Impedance ²	Z	---	100	---	ohm
Optical Wavelength	λ_o	1530	---	1565	nm
Side Mode Suppression Ratio	$SMSR$	30	---	---	dB

General Receiver Characteristics

Parameter	Symbol	Min.	Typical	Max.	Units
Differential Output Voltage	ΔV_o	0.8	---	1.6	V
Operating Wavelength	λ_c	1260	---	1600	nm
Differential Input Impedance ²	Z	---	100	---	Ohm
Rise/Fall Time (20% - 80%)	T_r/T_f	---	---	40	ps

Notes:

1. Module is designed for AC coupling. DC voltage will be filtered by internal capacitors.
2. Single ended will be 50 ohm for each signal line.
3. Refer to OptixCom "XENPAK Design Reference Guide" or IEEE 802.3ae for more design details.

Class 1 Laser Product
Complies with
21 CFR 1040.10 and 1040.11



Electrical Signal Characteristics

Parameter	Symbol	Min.	Typical	Max.	Units
1.2 V CMOS					
Input High Voltage	$V_{IL(MAX)}$	---	---	0.36	V
Input Low Voltage	$V_{IH(MIN)}$	0.84	---	1.25	V
Capacitance		---	---	320	pF
Pull Up Resistance	R_{pull}	10k	---	22k	Ohm
MDIO I/O					
Output Low Voltage	V_{OL}	-0.3	---	0.2	V
Output Low Current	I_{OL}	---	---	4	mA
Input High Voltage	V_{IH}	0.84	---	1.5	V
Input Low Voltage	V_{IL}	-0.3	---	0.36	V
Pull-Up Supply Voltage	V_{PULL}	1.14	1.2	1.26	
Input Capacitance	C_{IN}	---	---	10	pF
Load Capacitance	C_{LOD}	---	---	470	pF
External Pull-Up Resistance	E_{pull}	200	---	---	Ohm

Class 1 Laser Product
Complies with
21 CFR 1040.10 and 1040.11



Transmitter Electro-Optical Characteristics

Parameter	Symbol	Min.	Typical	Max.	Units
Optical Output Power ¹	P_o	0	---	+4	dBm
Optical Wavelength	λ_o	1530	1550	1565	nm
Extinction Ratio	ET	9	---	---	dB

Receiver Electro-Optical Characteristics

Parameter	Symbol	Min.	Typical	Max.	Units
Receiver Sensitivity ²	P_I	-24	---	-7	dBm
Receiver Sensitivity in OMA ²	P_{IOMA}	---	---	-22	dBm
RX Stressed Sensitivity in OMA ²	P_{SOMA}	---	---	-19	dBm
Reflectance	R_{rx}	---	---	-26	dB

Notes:

1. Output of coupling optical power into 9/125 μ m SMF.
2. Test at 10 Gb/s, 2³¹ – 1 PRBS data pattern, and > 1x10⁻¹² of Bit-Error-Rate (BER).
3. Refer to OptixCom "XENPAK Design Reference Guide" or IEEE 802.3ae for more design details.

Class 1 Laser Product
Complies with
21 CFR 1040.10 and 1040.11

