

155 Mb/s, 850 nm Multimode, 2 km Distance Dual LC SFP Package



Small Form Pluggable (SFP) Transceivers

Description

OptixCom's SFP transceiver offers advanced optical interconnect solution for general data communication links. This multimode fiber optics transceiver is designed with high performance 850 nm VCSEL light source. Dual LC connectors are used as standard interface and the package is compliant with Small Form Pluggable (SFP) specifications.

The module is compliant with SFP Multi-Source Agreement (MSA). It operates at 155 Mb/s and reaches 2 km of transmission distance with multimode fibers and >14 dB of power budget. This product is RoHS compliant.



Lead-Free


SFP-155SX-AT2K



Key Features

- 850 nm multimode, 155 Mb/s
- >14 dB power budget, 2 km reach
- Duplex LC connector optical interface
- Z-axis hot pluggable
- SFF-8472 MSA Compliant with DDM function
- AC coupling LVPECL differential I/O logics
- TTL Signal detect to monitor optical signals
- Single 3.3V power supply
- -20-85 °C operating temperatures available
- RoHS compliant

155 Mb/s, 2²³-1 NRZ data eye pattern



Applications

- ✓ FTTH, FTTX, ATM/SONET OC-3, SDH STM-1
- ✓ Fast Ethernet
- ✓ High speed I/O for file server
- ✓ Video over fiber links
- ✓ Media converter
- ✓ Data Communication for SAN and LAN
- ✓ Industrial Control Link
- ✓ Central offices routers and switches
- ✓ Mass storage systems interconnect
- ✓ Computer cluster cross-connect

Ordering Information

Part Number: SFP-155SX-AT2K

Description:

850 nm 155 Mb/s, multimode, SFP Fiber Optics Transceiver, 2 km reach, 0-70°C

* Add "-T" in the Part Number for extended temperature range -20-85 °C, i.e., SFP-155SX-AT2K-T.

Operating Conditions

Parameter	Min.	Typical	Max.	Units
Operate Temperature	0	25	70	°C
- T Transceivers	-20	25	85	°C
Data Rate	---	155	200	Mb/s
Supply Voltage	3.1	3.3	3.5	V
Supply Current	---	150	200	mA

U.S.A. Office: Optix Communications, Inc.

17901 Von Karman Avenue, Suite 600,
Irvine, CA 92614

Tel: (949) 679-5712 Fax: (949) 420-2134

<http://www.OptixCom.com>

<http://www.OpticalTransceiver.com>

Email: Support@OptixCom.com

Germany Office: OptixCom GmbH

Magdeburger Strasse 18, 66121
Saarbruecken, Germany

Tel: +49 (0)681 4013-5172

Absolute Maximum Ratings

Parameter	Symbol	Min.	Max.	Units
Storage Temperature	T_{st}	-40	85	°C
Supply Voltage	V_{cc}	-0.5	6.0	V
Input Voltage	V_{in}	-0.5	V_{cc}	V
Operating Current	I_{op}	---	400	mA
Output Current	I_o	---	50	mA

Transmitter Electro-Optical Characteristics

Parameter	Symbol	Min.	Typical	Max.	Units
Differential Input Voltage ¹	ΔV_i	0.4	---	2.0	V
Differential Input Impedance ²	Z	---	100	---	ohm
Optical Output Power ³	P_o	-10	---	-4	dBm
Optical Wavelength	λ_o	830	850	860	nm
Extinction Ratio	ET	9	---	---	dB
Spectral Width (rms)	$\Delta\lambda$	---	---	0.85	nm
Total Jitter	T_J	---	---	1	ns
Rise/Fall Time (10% - 90%)	T_r/T_f	---	---	2	ns
TX Disable Voltage – High	V_{DH}	2.4	---	V_{cc}	V
TX Disable Voltage - Low	V_{DL}	0	---	0.5	V
TX Fault Output - High	V_{FH}	2.4	---	V_{cc}	V
TX Fault Output - Low	V_{FL}	0	---	0.5	V
TX Disable Assert Time	T_{ass}	---	---	10	μs
TX Disable Deassert Time	T_{disass}	---	---	1.0	ms
Time to Initialize	T_{as}	---	---	300	ms
TX Fault from Fault to Assertion	T_{fault}	---	---	100	μs
TX Disable Time to Start Reset	T_{reset}	10	---	---	μs

Notes:

1. Module is designed for AC coupling. See the design guide for proper termination.
2. Single ended will be 50 ohm for each signal line.
3. Output of coupling optical power into 50/125 or 62.5/125 μm MMF.
4. Optical eye diagram is compliant with Telcordia GR-253-CORE and ITU-T G-957 standard.

Class 1 Laser Product
Complies with
21 CFR 1040.10 and 1040.11



Receiver Electro-Optical Characteristics

Parameter	Symbol	Min.	Typical	Max.	Units
Operating Wavelength	λ_c	770	---	860	nm
Receiver Overload	P_{max}	0	---	---	dBm
Receiver Sensitivity ¹	P_I	---	---	-24	dBm
Differential Output Voltage	ΔV_o	0.5	---	1.2	V
Differential Input Impedance ²	Z	---	100	---	Ohm
Optical Return Loss	OL	12	---	---	dB
Rise/Fall Time (10% - 90%)	T_r/T_f	---	1	2	ns
RX Signal Loss – Asserted	P_{RL+}	---	---	-24	dBm
RX Signal Loss – Deasserted	P_{RL-}	-45	---	---	dBm
Signal Detect Hysteresis	$P_{RL+} - P_{RL-}$	1	---	---	dB
Serial ID Clock Rate	f_c	---	---	100	kHz
RX Signal Loss Output - High	V_{RL+}	2.4	---	V_{cc}	V
RX Signal Loss Output - Low	V_{RL-}	0	---	0.5	V
RX Signal Loss Assert Time	T_{RL+}	---	---	100	μs
RX Signal Loss Deassert Time	T_{RL-}	---	---	100	μs

Notes:

1. Test at 155 Mb/s, 2²³ – 1 PRBS data pattern, and > 1x10⁻¹⁰ of Bit-Error-Rate (BER).
2. Single ended will be 50 ohm for each signal line.

Class 1 Laser Product
Complies with
21 CFR 1040.10 and 1040.11

